



Elbow may be added as an optional item.

FV-SP = Single Arm Valve
FV-DP = Double Arm Valve

Resin: Corrosion Grade - Isophthalic Polyester
Metallic parts are stainless steel. Float ball is polyethylene.
Flanges conform to standard ANSI 150 lb. drill patterns.
Standard configuration - single float arm is located on left side, looking into flow, unless otherwise noted.

I.D.	A	B	C	D	E	F	G-min.	G-max.	H	K
4"	9-1/2"	7-1/2"	8"	6-5/8"	10-1/2"	21"	36"	54"	26"	1-1/4"
6"	11-1/2"	9-1/2"	8"	7-5/8"	11-1/8"	22-1/4"	36"	54"	25-1/2"	1-1/4"
8"	14"	11-3/4"	8"	8-7/8"	12-3/8"	24-3/4"	36"	54"	25"	1-1/2"
10"	16-1/2"	14-1/4"	8"	9-7/8"	--	26-3/4"	36"	54"	24-1/2"	1-1/2"
12"	19-1/2"	17"	8"	11-7/8"	--	28-3/4"	36"	54"	24"	1-1/2"

MER-MADE FILTER

PO Box 306 Denmark, SC 29042

P: 803-793-4265 F: 803-793-4332

www.meremade.com

Customer:

Project:

Dwg.T-11479

FV-SP or FV-DP Float Valve

Rev. 05-19